

SERVICE TYPE: Training _____ Emergency Response _____ Standby _____ Maintenance _____

Name: _____ Date: _____ Odometer: _____ Hours: _____ VEH04 Inspection

CANAM UTVs (5535, 5537, 5538)

CHECK AFTER EACH APPARATUS USE

	Required Status	OK	Exception Status
Fuel Level	Minimum ¾ Full (Gasoline)		
Headlights	Turned OFF		
Chassis Lights	All operational		
Emergency Lights	All operational		
2wd/4wd/6wd	Set to 2wd		
Transmission	Placed in PARK		
Radio	Response Mode BCFD-S, Default scan ON, Volume level SET for in-station level		
Ignition Switch	OFF		
Shore Power	Connected, confirm power ON		
Spot thermometer	In Glovebox		
Map Book	Present, all Topos & reference cards in place		
Tires	Visually inspect, thump to check pressure		
SCBA Tanks	OFF –Full		
H2O/Air Valves	OFF		
Water Tank Level	Full with foam added		
Wildland Hand Tools	Confirm in bed		
Chainsaw	Present - chainsaw Manager will maintain		
Seat and steering wheel clean	Wipe down if your hand comes away dirty clean		

CANAM UTVs (5535, 5537, 5538)

CHECK AFTER EACH APPARATUS USE COMPLETE MONTHLY OR AFTER MAJOR INCIDENT

	Required Status	OK	Exception Status
Engine Oil Level	5W/40 Synthetic blend oil (dipstick under bed/cargo box; passenger side)		
Radiator Fluid Level	Visible, level half-way up sight glass		
Batteries	Terminals clean and tight (located under bed/cargo box; driver side, behind shore power outlet)		
Drive Belt	Clean, tight & in good condition (located under bed/cargo box; remove plastic cover)		
Air Filter	Visually check, blow out dirt (located under bed)		
Tires	Visually inspect, & verify pressure at 10psi		
Winch – front and rear	Operational – power in and out 2+ feet, leave in Free-Wheel Mode (knob on left side). Verify that tree strap or chain is present in cargo box.		
Water Tank Level	Full of water with foam concentrate		
Control Panel valves	Confirm operational - Spray foam to keep foam from congealing. Refill water, add foam. <i>If insufficient water flow, use winch to pick up water unit, clean filter on bottom of passenger side.</i>		
Hoses and nozzles	Secured in cargo bed		
Water Packs (2)	Full & ready for use		
Drinking H2O	Present in Cargo box		
Drive for at least 3 minutes	Verify steering and suspension feels tight. Verify that brakes seem adequate, no grabbing or noise. Verify parking brake will hold on moderate+ hill. Verify belt not slipping and that clutch is not excessively grabby. <i>Replace belt if necessary. Order a new spare or report up. Verify new spare is in place within 7 days.</i>		
Seat, steering wheel, floor, body, controls, and tools all clean	Wipe down and wash with soapy water if your hand comes away dirty.		